

01 Jun 09

SALES SPECIFICATIONS

Ethylene Glycol Antifreeze Grade Specified Material: 000132327-S

SPECIFICATION	ETHYLENE GLYCOL ANTIFREEZE GRADE
Purity, %wt, minimum	95.0
Diethylene Glycol, %wt, maximum	5.0
Acidity, ppm, maximum, as Acetic Acid	100
Water, %wt, maximum	0.5
Color, Platinum-Cobalt Units, maximum	25
Appearance	Pass

For material made from recovered By-Product Glycol produced at Union Carbide's West Virginia Plant, a wholly owned subsidiary of The Dow Chemical Company, esters are less than 300 ppm calculated as acetic acid.

* Typical values for Specific Gravity (20/20C): 1.1130 to 1.1170

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

*Ethylene Glycol Antifreeze Grade
Last Updated: 19 Jan 07*