

01 Jun 09

SALES SPECIFICATIONS

Ethylene Glycol Commercial Polyester Grade Specified Material: 00155313-S

SPECIFICATION	ETHYLENE GLYCOL COMMERCIAL POLYESTER GRADE
Purity, %wt, minimum	99.9
Diethylene Glycol, %wt, maximum	0.05
Acidity, ppm, maximum, as Acetic Acid	20
Iron, ppm, maximum	0.1
Chlorides, ppm, maximum	0.2
UV Transmit @ 220nm, %T, minimum	70.0
UV Transmit @ 275nm, %T, minimum	90.0
UV Transmit @ 350nm, %T, minimum	98.0
Water, %wt, maximum	0.050
Color, Platinum-Cobalt Units, maximum	5
Appearance	Pass

Typical values for specific Gravity (20/20°C): 1.1151 to 1.1156

Typical values for Refractive Index at 20°C: 1.4305 to 1.4330

Typical values for Ash content: < 20ppm

NOTICE: No freedom from any patent owned by Seller or others is to be inferred. Because use conditions and applicable laws may differ from one location to another and may change with time, Customer is responsible for determining whether products and the information in this document are appropriate for Customer's use and for ensuring that Customer's workplace and disposal practices are in compliance with applicable laws and other governmental enactments. Seller assumes no obligation or liability for the information in this document. NO WARRANTIES ARE GIVEN; ALL IMPLIED WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE ARE EXPRESSLY EXCLUDED.

*Ethylene Glycol Commercial Polyester Grade
Last Updated: 30 Apr 07*