

**Trade name: ETHYLENE GLYCOL POLYESTER GRADE**

**Issue Date: 11/15/2025**

**Version: 19.0**

MEGLOBAL CANADA ULC encourages and expects you to read and understand the entire SDS, as there is important information throughout the document. We expect you to follow the precautions identified in this document unless your use conditions would necessitate other appropriate methods or actions.

---

## 1. IDENTIFICATION

---

### Product identifier

**Trade name:** ETHYLENE GLYCOL POLYESTER GRADE

**CAS Number:**

107-21-1

### Other means of identification

**EC number:**

203-473-3

**Index number:**

603-027-00-1

### Application of the substance / the mixture:

Industrial use.

Chemical intermediate, e.g. for manufacture of polyester resins. De-icing fluid. Heat transfer fluid.

It is recommended that you use this product in a manner consistent with the recommended use. If your intended use is not consistent with the recommended use, please contact our Customer Information Group (telephone number in Section 1 of this document).

### Uses advised against

Production of tobacco products Generation of artificial smoke Electronic cigarettes (e-cigarettes)  
Applications with direct or indirect food or potable water contact Any application where the product is to be purposely used as a non-reactant component where the potential for sufficient human contact and/or ingestion exists Freezer gel packs and heating packs Glues and pastes Manufacturing of munitions Sprinkler systems Deicing of road or sidewalks Deicing of aircraft lavatories Consumer or hospital usage for deodorizing or air "purifying" purposes by spraying as an aerosol Fluid for pressure testing piping Pharmaceutical Use Treatment of wood rot and fungus in marine applications.

### Details of the supplier of the safety data sheet

#### Manufacturer/Supplier:

MEGLOBAL CANADA ULC  
1300, 1969 UPPER WATER STREET  
PURDY'S WHARF TOWER II  
HALIFAX NS B3J 3R7  
CANADA

Customer Information Number: 1-844-634-5622

meglobaluscsrs@meglobal.biz

Fax: +1-281-207-0267

### EMERGENCY TELEPHONE NUMBER

**Local Emergency Contact:** +1-703-527-3887 or 1-800-424-9300 (CHEMTREC)

---

**2. HAZARDS IDENTIFICATION**

---

**Classification of the substance or mixture**

Acute Toxicity (Oral) - Category 4

H302Harmful if swallowed.

Specific target organ toxicity (single exposure) –  
Category 1

H370Causes damage to organs.

**Label elements****GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

**Hazard pictograms**

GHS07



GHS08

**Signal word** Danger**Hazard-determining components of labeling:**

Ethylene glycol

**Hazard statements**

H302 Harmful if swallowed.

H370 Causes damage to organs.

**Precautionary statements:**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

**Additional Information:****Information pertaining to particular dangers for man and environment:****Classification system:****NFPA ratings (scale 0 - 4)**

Health = 0

Fire = 1

Reactivity = 0

**HMIS-ratings (scale 0 - 4)**

Health = 0

Fire = 1

Reactivity = 0

---

**3. COMPOSITION/INFORMATION ON INGREDIENTS**

---

**Chemical characterization: Substances****CAS No. Description**

107-21-1 Ethylene glycol

**Identification number(s)****EC number:** 203-473-3**Index number:** 603-027-00-1

<b>Hazardous Components:</b>		
107-21-1	<b>Ethylene glycol</b> Specific target organ toxicity (single exposure) – Category 1, H370; Acute Toxicity (Oral) - Category 4, H302	99%% w/w

---

**4. FIRST AID MEASURES**

---

**Description of first aid measures****General information:**

First Aid responders should pay attention to self-protection and use the recommended protective clothing (chemical resistant gloves, splash protection). If potential for exposure exists refer to Section 8 for specific personal protective equipment.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48 hours after the accident.

**After inhalation:** Move patient to fresh air, if symptom arise consult a doctor.

**After skin contact:**

Immediately flush skin with water while removing contaminated clothing and shoes. Get medical attention if symptoms occur. Wash clothing before reuse. Destroy contaminated leather items such as shoes, belts, and watchbands. Suitable emergency safety shower facility should be immediately available.

**After eye contact:**

Flush eyes thoroughly with water for several minutes. Remove contact lenses after the initial 1-2 minutes and continue flushing for several additional minutes. If effects occur, consult a physician, preferably an ophthalmologist.

**After swallowing:**

Do not induce vomiting. Seek medical attention immediately. If person is fully conscious give 1 cup or 8 ounces (240 ml) of water. If medical advice is delayed and if an adult has swallowed several ounces of chemical, then give 3-4 ounces (1/3-1/2 Cup) (90-120 ml) of hard liquor such as 80 proof whiskey. For children, give proportionally less liquor at a dose of 0.3 ounce (1 1/2 tsp.) (8 ml) liquor for each 10 pounds of body weight, or 2 ml per kg body weight [e.g., 1.2 ounce (2 1/3 tbsp.) for a 40 pound child or 36 ml for an 18 kg child].

**Most important symptoms and effects, both acute and delayed**

Aside from the information found under Description of first aid measures (above) and Indication of immediate medical attention and special treatment needed (below), any additional important symptoms and effects are described in Section 11: Toxicology Information.

**Indication of any immediate medical attention and special treatment needed**

Notes to physician: If several ounces (60 - 100 ml) of ethylene glycol have been ingested, early administration of ethanol may counter the toxic effects (metabolic acidosis, renal damage). Consider

hemodialysis or peritoneal dialysis & thiamine 100 mg plus pyridoxine 50 mg intravenously every 6 hours. If ethanol is used, a therapeutically effective blood concentration in the range of 100 - 150 mg/dl may be achieved by a rapid loading dose followed by a continuous intravenous infusion. Consult standard literature for details of treatment. 4-Methyl pyrazole (Antizol®) is an effective blocker of alcohol dehydrogenase and should be used in the treatment of ethylene glycol (EG), di- or triethylene glycol (DEG, TEG), ethylene glycol butyl ether (EGBE), or methanol intoxication if available. Fomepizole protocol (Brent, J. et al., New England Journal of Medicine, Feb. 8, 2001, 344:6, p. 424-9): loading dose 15 mg/kg intravenously, follow by bolus dose of 10 mg/kg every 12 hours; after 48 hours, increase bolus dose to 15 mg/kg every 12 hours. Continue fomepizole until serum methanol, EG, DEG, TEG or EGBE are undetectable. The signs and symptoms of poisoning include anion gap metabolic acidosis, CNS depression, renal tubular injury, and possible late stage cranial nerve involvement. Respiratory symptoms, including pulmonary edema, may be delayed. Persons receiving significant exposure should be observed 24-48 hours for signs of respiratory distress. In severe poisoning, respiratory support with mechanical ventilation and positive end expiratory pressure may be required. Maintain adequate ventilation and oxygenation of the patient. If lavage is performed, suggest endotracheal and/or esophageal control. Danger from lung aspiration must be weighed against toxicity when considering emptying the stomach. If burn is present, treat as any thermal burn, after decontamination. Treatment of exposure should be directed at the control of symptoms and the clinical condition of the patient.

---

## 5. FIREFIGHTING MEASURES

---

### Extinguishing media

#### Suitable extinguishing agents:

Water fog or fine spray. Dry chemical fire extinguishers. Carbon dioxide fire extinguishers. Foam. Alcohol resistant foams (ATC type) are preferred. General purpose synthetic foams (including AFFF) or protein foams may function, but will be less effective.

**For safety reasons unsuitable extinguishing agents:** Do not use direct water stream. May spread fire.

#### Special hazards arising from the substance or mixture

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and/or irritating. Combustion products may include and are not limited to: Carbon monoxide. Carbon dioxide. Nitrogen oxides.

Container may rupture from gas generation in a fire situation. Violent steam generation or eruption may occur upon application of direct water stream to hot liquids.

#### Advice for firefighters

Fire Fighting Procedures: Keep people away. Isolate fire and deny unnecessary entry. Use water spray to cool fire exposed containers and fire affected zone until fire is out and danger of reignition has passed. Fight fire from protected location or safe distance. Consider the use of unmanned hose holders or monitor nozzles. Immediately withdraw all personnel from the area in case of rising sound from venting safety device or discoloration of the container. Burning liquids may be extinguished by dilution with water. Do not use direct water stream. May spread fire. Move container from fire area if this is possible without hazard. Burning liquids may be moved by flushing with water to protect personnel and minimize property damage.

#### Protective equipment:

Wear positive-pressure self-contained breathing apparatus (SCBA) and protective fire fighting clothing (includes fire fighting helmet, coat, trousers, boots, and gloves). If protective equipment is not available or not used, fight fire from a protected location or safe distance.

---

## 6. ACCIDENTAL RELEASE MEASURES

---

### **Personal precautions, protective equipment and emergency procedures**

Isolate area. Keep unnecessary and unprotected personnel from entering the area. Refer to section 7, Handling, for additional precautionary measures. Use appropriate safety equipment. For additional information, refer to Section 8, Exposure Controls and Personal Protection.

Mount respiratory protective device.

### **Environmental precautions:**

Prevent from entering into soil, ditches, sewers, waterways and/or groundwater. See Section 12, Ecological Information.

Dilute with plenty of water.

### **Methods and material for containment and cleaning up:**

Contain spilled material if possible. Collect in suitable and properly labeled containers. Small spills: Absorb with materials such as: Cat litter. Sand. Sawdust. Zorb-all®. Hazorb®. Large spills: Dike area to

contain spill. Pump into suitable and properly labeled containers. See Section 13, Disposal Considerations, for additional information.

Ensure adequate ventilation.

Dispose contaminated material as waste according to section 13.

### **Reference to other sections**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

---

## 7. HANDLING AND STORAGE

---

### **Precautions for safe handling**

Do not swallow. Avoid contact with eye, skin and clothing. Wash thoroughly after handling. Spills of these organic materials on hot fibrous insulations may lead to lowering of the autoignition temperatures possibly resulting in spontaneous combustion. See Section 8, EXPOSURE CONTROLS AND PERSONAL PROTECTION.

Ensure good ventilation/exhaustion at the workplace.

Prevent formation of aerosols.

### **Information about protection against explosions and fires:**

Keep respiratory protective device available.

### **Conditions for safe storage, including any incompatibilities**

Do not store near food, foodstuffs, drugs or potable water supplies. Additional storage and handling information on this product may be obtained by calling your sales or customer service contact. Ask for a product brochure.

**Requirements to be met by storerooms and receptacles:** No special requirements.

**Information about storage in one common storage facility:** Not required.

**Further information about storage conditions:** None.

**Specific end use(s)** No further relevant information available.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Control parameters

#### Components with limit values that require monitoring at the workplace:

##### 107-21-1Ethylene glycol

EL (Canada)	STEL: 20* mg/m <sup>3</sup> TWA: 10* mg/m <sup>3</sup> Ceiling: 100* mg/m <sup>3</sup> , 50** ppm *total, aerosol only; **Vapour
EV (Canada)	Ceiling: 100 mg/m <sup>3</sup>
TLV (USA)	STEL: 10** mg/m <sup>3</sup> , 50* ppm TWA: 25* ppm
WEEL (USA)	*vapor fraction:**inh. fraction, aerosol only, A4 I (2)

**Additional information:** The lists that were valid during the creation were used as basis.

### Exposure controls

#### Personal protective equipment

##### General protective and hygienic measures:

Use local exhaust ventilation, or other engineering controls to maintain airborne levels below exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, general ventilation should be sufficient for most operations. Local exhaust ventilation may be necessary for some operations.

Keep away from foodstuffs, beverages and feed.

Store protective clothing separately.

##### Breathing equipment:

Respiratory protection should be worn when there is a potential to exceed the exposure limit requirements or guidelines. If there are no applicable exposure limit requirements or guidelines, wear respiratory protection when adverse effects, such as respiratory irritation or discomfort have been experienced, or where indicated by your risk assessment process. For most conditions, no respiratory protection should be needed; however, if material is heated or sprayed, use an approved air-purifying respirator. Use the following CE approved air-purifying respirator: Organic vapor cartridge with a particulate pre-filter, type AP2.

##### Protection of hands:



Protective gloves

Use gloves chemically resistant to this material when prolonged or frequently repeated contact could occur.

Use gloves with insulation for thermal protection, when needed. If hands are cut or scratched, use gloves chemically resistant to this material even for brief exposures.

##### Material of gloves

Natural rubber, NR

Neoprene gloves

Nitrile rubber, NBR

Polyethylene gloves

PVA gloves

PVC gloves

Ethyl vinyl alcohol laminate, EVAL

NOTICE: The selection of a specific glove for a particular application and duration of use in a workplace should also take into account all relevant workplace factors such as, but not limited to: Other chemicals which may be handled, physical requirements (cut/puncture protection, dexterity, thermal protection), potential body reactions to glove materials, as well as the instructions/specifications provided by the glove supplier.

#### Penetration time of glove material

The exact break through time has to be found out by the manufacturer of the protective gloves and has to be observed.

#### Eye protection:



Tightly sealed goggles

Goggles recommended during refilling.

#### Body protection:

When prolonged or frequently repeated contact could occur, use protective clothing chemically resistant to this material. Selection of specific items such as faceshield, boots, apron, or full-body suit will depend on the task. When handling hot material, protect skin from thermal burns as well as from skin absorption.

---

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### Information on basic physical and chemical properties

#### General Information

Physical state	Liquid
Color:	Colorless.
Odor:	Sweet
Odor threshold:	No test data available
Melting point/Melting range:	Not applicable to liquids.
Boiling point/Boiling range:	197.4 °C (Literature)
Flammability:	Not applicable.
Explosion limits:	
Lower:	3.2 Vol % (Literature)
Upper:	53 Vol % (Literature)
Flash point:	111 °C (Literature/Closed cup)
Auto-ignition temperature:	398 °C (Literature)
Decomposition temperature:	No test data available
pH-value:	9 (Literature)
Viscosity:	
Kinematic:	Not determined.
Dynamic at 20 °C:	19.83 mPas (Literature)
Solubility in / Miscibility with	
Water at 20 °C:	100 % (Literature)
Partition coefficient (n-octanol/water):	Not determined.
Vapor pressure at 20 °C:	0.067 hPa (Literature)
Vapor pressure:	
Density at 20 °C:	>1.11 g/cm <sup>3</sup>
Relative density at 20 °C	1.115 (water=1 / Literature)
Vapor density at 20 °C	2.1 g/cm <sup>3</sup> (air=1 / Literature)
Particle characteristics	Not applicable.

Other information	Molecular weight: 62 g/mol (Literature) Molecular formula: HOC2H4OH
	NOTE: The physical data presented above are typical values and should not be constituted as a specification.
Appearance:	
Form:	Liquid.
Danger of explosion:	Product does not present an explosion hazard. Not determined.
Flammability Limits:	
Lower:	Not Determined.
Upper:	Not Determined.
Solids content:	0.0 %
Oxidizing properties	Not determined.
Evaporation rate	0.01 (Butyl acetate = 1)

---

## 10. STABILITY AND REACTIVITY

---

**Reactivity:** No data available

**Chemical stability:** Thermally stable at recommended temperatures and pressures.

**Thermal decomposition / conditions to be avoided:**

No decomposition if used according to specifications.

**Possibility of hazardous reactions** Polymerization will not occur.

**Conditions to avoid:**

Exposure to elevated temperatures can cause product to decompose. Generation of gas during decomposition can cause pressure in closed systems.

**Incompatible materials:** Avoid contact with: Strong acids. Strong bases. Strong oxidizers

**Hazardous decomposition products:**

Decomposition products depend upon temperature, air supply and the presence of other materials. Decomposition products can include and are not limited to: Aldehydes. Alcohols. Ethers.

---

## 11. TOXICOLOGICAL INFORMATION

---

### Information on toxicological effects

#### Acute toxicity:

Harmful if swallowed

#### Acute oral toxicity

Oral toxicity is expected to be moderate in humans due to ethylene glycol even though tests with animals show a lower degree of toxicity. Ingestion of quantities (approximately 65 mL (2 oz.) for diethylene glycol or 100 mL (3 oz.) for ethylene glycol) has caused death in humans. May cause nausea and vomiting. May cause abdominal discomfort or diarrhea. Excessive exposure may cause central nervous system effects, cardiopulmonary effects (metabolic acidosis), and kidney failure.

LD50, Rat, male and female, 7,712 mg/kg

Lethal Dose, Human, adult, 100 ml Estimated.

**Acute dermal toxicity**

Prolonged skin contact is unlikely to result in absorption of harmful amounts. Repeated skin exposure to large quantities may result in absorption of harmful amounts. Massive contact with damaged skin or of material sufficiently hot to burn skin may result in absorption of potentially lethal amounts.

LD50, Rabbit, > 10,600 mg/kg

LD50, Mouse, male and female, > 3,500 mg/kg

**Acute inhalation toxicity**

At room temperature, exposure to vapor is minimal due to low volatility. With good ventilation, single exposure is not expected to cause adverse effects. If material is heated or areas are poorly ventilated, vapor/mist may accumulate and cause respiratory irritation and symptoms such as headache and nausea.

LC50, Rat, male and female, 6 Hour, dust/mist, > 2.5 mg/l

**LD/LC50 values that are relevant for classification:****107-21-1 Ethylene glycol**

Oral	LD50	7,712 mg/kg (Rat)
Dermal	LD50	>3,500 mg/kg (mouse) >10,600 mg/kg (rabbit)
Inhalative	LC50	>2.5 mg/L (Rat)

**Primary irritant effect:****on the skin:**

Brief contact is essentially nonirritating to skin.

Prolonged contact may cause slight skin irritation with local redness.

Repeated contact may cause skin irritation with local redness.

**on the eye:**

May cause slight eye irritation.

Corneal injury is unlikely.

Vapor or mist may cause eye irritation.

**Sensitization:**

Did not cause allergic skin reactions when tested in guinea pigs.

For respiratory sensitization:

No relevant data found.

**Germ cell mutagenicity**

In vitro genetic toxicity studies were negative. Animal genetic toxicity studies were negative.

**Carcinogenicity** Ethylene glycol did not cause cancer in long-term animal studies.

**Reproductive toxicity**

Ingestion of large amounts of ethylene glycol has been shown to interfere with reproduction in animals  
Teratogenicity

Based on animal studies, ingestion of very large amounts of ethylene glycol appears to be the major and possibly only route of exposure to produce birth defects. Exposures by inhalation or skin contact, the primary routes of occupational exposure, had minimal effect on the fetus, in animal studies.

**Specific target organ toxicity - single exposure**

Causes damage to organs.

Classification based on Health Canada's direction for Ethylene Glycol.

**Aspiration hazard** Based on physical properties, not likely to be an aspiration hazard.

**Additional toxicological information:****Carcinogenic categories**

**IARC (International Agency for Research on Cancer)** Substance is not listed.

NTP (National Toxicology Program) Substance is not listed.

## 12. ECOLOGICAL INFORMATION

### Toxicity

#### Aquatic toxicity:

Acute toxicity to fish

Material is not classified as dangerous to aquatic organisms (LC50/EC50/IC50/LL50/EL50 greater than 100 mg/L in most sensitive species).

LC50, Pimephales promelas (fathead minnow), static test, 96 Hour, 72,860 mg/l, Other guidelines

Acute toxicity to aquatic invertebrates

EC50, Daphnia magna (Water flea), static test, 48 Hour, > 100 mg/l, OECD Test Guideline 202 or Equivalent

Acute toxicity to algae/aquatic plants

ErC50, Pseudokirchneriella subcapitata (green algae), 96 Hour, Growth rate inhibition, 6,500 - 13,000 mg/l,

Other guidelines

Toxicity to bacteria

EC50, activated sludge, 30 min, 225 mg/l, OECD 209 Test

107-21-1 Ethylene glycol	
LC50/96h (static)	72,860 mg/L (Pimephales Promelas (Fathead Minnow)) static test
EC50/48h (static)	>100 mg/L (Daphnia Magna) (OECD 202 or equivalent) static test
ErC50 (96h)	6,500-13,000 mg/L (Pseudokirchneriella Subcapitata) Growth inhibition
EC50/30min	225 mg/L (Activated Sludge) (OECD 209)

### Persistence and degradability

Biodegradability: Material is readily biodegradable. Passes OECD test(s) for ready biodegradability. Material is ultimately biodegradable (reaches > 70% mineralization in OECD test(s) for inherent biodegradability).

Biodegradation: 90 - 100 %

Exposure time: 20 d

Method: OECD Test Guideline 301A or Equivalent

10-day Window: Pass

Biodegradation: 82 - 98 %

Exposure time: 28 d

Method: OECD Test Guideline 302C or Equivalent

Theoretical Oxygen Demand: 1.51 mg/mg

10-day Window: Not applicable

Theoretical Oxygen Demand: 1.29 mg/mg

#### Bioaccumulative potential

Bioaccumulation: Bioconcentration potential is low (BCF < 100 or Log Pow < 3).

Partition coefficient: n-octanol/water(log Pow): -1.36 Measured

**Mobility in soil**

Given its very low Henry's constant, volatilization from natural bodies of water or moist soil is not expected to be an important fate process.

Potential for mobility in soil is very high (Koc between 0 and 50).

Partition coefficient (Koc): 1 Estimated.

**Results of PBT and vPvB assessment**

**PBT:** No PBT.

**vPvB:** No vPvB.

**Other adverse effects**

This substance is not on the Montreal Protocol list of substances that deplete the ozone layer.

**Additional ecological information****General notes:**

Water hazard class 1 (Assessment by list): slightly hazardous for water

Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

---

**13. DISPOSAL CONSIDERATIONS**

---

**Waste treatment methods**

DO NOT DUMP INTO ANY SEWERS, ON THE GROUND, OR INTO ANY BODY OF WATER. All disposal practices must be in compliance with all Federal, State/Provincial and local laws and regulations. Regulations may vary in different locations. Waste characterizations and compliance with applicable laws are the responsibility solely of the waste generator. WE HAVE NO CONTROL OVER THE MANAGEMENT PRACTICES OR MANUFACTURING PROCESSES OF PARTIES HANDLING OR USING THIS MATERIAL. THE INFORMATION PRESENTED HERE PERTAINS ONLY TO THE PRODUCT AS SHIPPED IN ITS INTENDED CONDITION AS DESCRIBED IN SDS SECTION:

Composition Information. FOR UNUSED & UNCONTAMINATED PRODUCT, the preferred options include sending to a licensed, permitted: Recycler. Reclaimer. Incinerator or other thermal destruction device.

**Recommendation:** Do not allow product to reach sewage system.

**Uncleaned packagings:****Recommendation:**

Disposal must be made according to official regulations.

Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

Empty containers must be recycled or disposed of through an approved waste management unit.

Waste characterization and compliance with applicable laws are the sole responsibility of the waste generator. Do not reuse containers for any purpose.

**Recommended cleansing agent:** Water, if necessary with cleaning agents.

---

**14. TRANSPORT INFORMATION**

---

**UN-Number**  
DOT/TDG, ADR, IMDG, IATA Not applicable.

**UN proper shipping name**  
DOT/TDG, ADR, IMDG, IATA Not applicable.

**Transport hazard class(es)**  
DOT/TDG, ADR, ADN, IMDG, IATA  
Class Not applicable.

**Packing group**  
DOT/TDG, ADR, IMDG, IATA Not applicable.

**Environmental hazards:** Not applicable.

**Classification for SEA transport (IMO-IMDG):**

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code** Product Name: Ethylene Glycol  
Pollution Category: Z  
Ship Type: 3  
Fire Protection: AC

**Transport/Additional Information:** This product may be transported under nitrogen padding. Nitrogen is an odorless and invisible gas. Exposure to a nitrogen enriched environment may cause asphyxiation or death. Personnel must observe strict safety precautions when involved with a confined space entry.

**Special precautions for user:** Refer to Section 7 (Handling & Storage) for special precautions which personnel needs to be aware of or needs to comply with in connection with transport.

This information is not intended to convey all specific regulatory or operational requirements/information relating to this product. Transportation classifications may vary by container volume and may be influenced by regional or country variations in regulations. Additional transportation system information can be obtained through an authorized sales or customer service representative. It is the responsibility of the transporting organization to follow all applicable laws, regulations and rules relating to the transportation of the material.

---

**15. REGULATORY INFORMATION**

---

**Safety, health and environmental regulations/legislation specific for the substance or mixture**

No further relevant information available.

**Sara**

**Section 355 (extremely hazardous substances):** Substance is not listed.

**Section 313 (Specific toxic chemical listings):** Substance is listed.

**USA - TSCA (Toxic Substances Control Act):** ACTIVE

**Canadian Domestic Substances List (DSL)** Substance is listed.

**Canadian Non-Domestic Substances List (NDSL)** Substance is not listed.

**Canadian Ingredient Disclosure list (limit 0.1%)** Substance is not listed.

**Canadian Ingredient Disclosure list (limit 1%)** Substance is listed.

**GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



GHS07



GHS08

**Signal word** Danger

**Hazard-determining components of labeling:**

Ethylene glycol

**Hazard statements**

H302 Harmful if swallowed.

H370 Causes damage to organs.

**Precautionary statements**

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

P301+P312 IF SWALLOWED: Call a POISON CENTER/doctor if you feel unwell.

P308+P311 IF exposed or concerned: Call a POISON CENTER/doctor.

P321 Specific treatment (see on this label).

P330 Rinse mouth.

P405 Store locked up.

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

---

**16. OTHER INFORMATION**

---

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

**Revision****Identification Number:** 101232907 / MS01**Date of preparation:** 11/15/2025 / Version: 19.0**Date of previous version:** 01/31/2025 / Version: 18.1**Abbreviations and acronyms:**

ADR: Accord relatif au transport international des marchandises dangereuses par route (European Agreement Concerning the International Carriage of Dangerous Goods by Road)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances

ELINCS: European List of Notified Chemical Substances

CAS: Chemical Abstracts Service (division of the American Chemical Society)

NFPA: National Fire Protection Association (USA)

HMIS: Hazardous Materials Identification System (USA)

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

**Information Source and References**

This SDS is prepared by B-lands Consulting.

MEGGLOBAL CANADA ULC urges each customer or recipient of this SDS to study it carefully and consult appropriate expertise, as necessary or appropriate, to become aware of and understand the data contained in this SDS and any hazards associated with the product. The information herein is provided in good faith and believed to be accurate as of the effective date shown above. However, no warranty, express or implied, is given. Regulatory requirements are subject to change and may differ between various locations. It is the buyer's/user's responsibility to ensure that his activities comply with all federal, state, provincial or local laws. The information presented here pertains only to the product as shipped. Since conditions for use of the product are not under the control of the manufacturer, it is the buyer's/user's duty to determine the conditions necessary for the safe use of this product. Due to the proliferation of sources for information such as manufacturer-specific SDSs, we are not and cannot be responsible for SDSs obtained from any source other than ourselves. If you have obtained an SDS from another source or if you are not sure that the SDS you have is current, please contact us for the most current version.